

Get tough!

Welding, hot batteries or similar – PRYSMIAN H01N2-D cables always get the job done.



Hard-wearing

Thanks to a cross-linked special compound in the outer sheath, PRYSMIAN H01N2-D can handle a whole lot of severe beating, liquids and heat.

Flexible

The compound in the sheath not only makes the cable very durable, the highly elastomeric material makes the cable extremely pliable, too.

Weather-proof

Operating from -40 °C to +85 °C, in rain, snow or sun, this weather beater won't budge before you do.



Welding, hot batteries or similar – PRYSMIAN H01N2-D cables always get the job done.

If you're in search for a cable not afraid of getting its hands dirty and always ready to take the heat, have a look at PRYSMIAN H01N2-D. This roughneck cable pushes the power forward to any type of gear working under hot conditions. May it be high mechanical stress, inside or outdoors, in rain, snow or sun – PRYSMIAN H01N2-D won't yield for anything.

PRYSMIAN H01N2-D CABLES

Hard-hitting work sometimes need extra elbow grease to reach the wished-for results. It might have to be done in areas with lots of heavy machinery, in small and cramped places, or in hot, or cold, environments. To make sure the gear is up for the task and fed with all the electricity it needs without any interruptions, an equally tough, or even tougher, cable is required.

PRYSMIAN H01N2-D is intended for use with hand-held electrodes at 100 V in dry, humid and moist rooms as well as outdoors, where the cables are subjected to high mechanical stresses. It can be used for welding robots, in shipyards, operated lines and spot welding. This cable works also perfect as battery cable or in battery storage systems. In other respects the specifications of DIN EN 50565-2 apply.

MAIN FEATURES

- ✓ Operating temperature from -40 °C to +85 °C
- ✓ Impact resistant
- ✓ Resistant to high temperatures, ozone, oils, greases and gas
- ✓ Highly flexible also at very low temperatures



TECHNICAL DATA



PRYSMIAN H01N2-D 100/100 V	
Global data	
Brand	PRYSMIAN
Type designation	H01N2-D
Standard	DIN EN 50525-2-81
Design features	
Conductor	Bare copper, acc. to IEC 60228 class 6, multi-flexible (F)
Conductor shape	Round (R)
Outer sheath	Cross-linked elastomeric special compound: requirements in acc. with DIN EN 50363-2-2: EMS
Outer sheath colour	Black
Electrical parameters	
Rated voltage	100/100 V
Max. permissible operating voltage AC	0.110/0.110 kV
Max. permissible operating voltage DC	0.165/0.165 kV
AC test voltage	1 kV

PRYSMIAN H01N2-D 100/100 V	
Chemical parameters	
Flame propagation	DIN EN 60332-1-2
Resistance to oil	DIN EN 60811-404
Thermal parameters	
Max. operating temperature of the conductor	85°C
Max. short circuit temperature of the conductor	250°C
Ambient temperature for fix installation min.	-40°C
Ambient temperature in fully flex. operation min.	-40°C
Mechanical parameters	
Max. tensile load on the conductor	15 N/mm ²
Bending radii min.	Acc. to DIN VDE 0298 part 3

PRYSMIAN H01N2-D 100/100 V							
Number of cores x cross section	Part number	Outer diameter (approx.) mm	Weight (approx.) kg/km	Current rating for single cycle operation over a maximum period of 5 minutes (A)			
				100 % duty cycle	85 % duty cycle	60 % duty cycle	35 % duty cycle
1x10	20364553	8.54	144	100	103	108	122
1x16	20364554	9.59	204	135	145	175	230
1x25	20364555	10.57	283	180	195	230	300
1x35	20364556	11.72	378	225	245	290	375
1x50	20364557	13.52	529	285	305	365	480
1x70	20364560	16.21	742	355	385	460	600
1x95	20364559	17.37	944	430	470	560	730
1x120	20364558	19.57	1210	500	540	650	850

PRYSMIAN H01N2-D 100/100 V							
Ambient temperature	25°C	30°C	35°C	40°C	45°C	50°C	55°C
De-rating factor	1.0	0.96	0.91	0.87	0.82	0.76	0.71

Please check our homepage: www.prysmiangroup.de for more details.

COMMITTED TO SERVICE

Effective and efficient production secures the demands for cables.

"The key to success is a strong collaboration between process engineering, maintenance and production".

Sezgin Islamoglu, Operations Director CEE, Prysmian

To make sure we can provide you with all the cables that you need, we make recurring investments in our manufacturing plants. By making sure we are up to date, we are always ready to provide customers and communities worldwide with cable solutions based on state-of-the-art technology, consistent excellence in execution and in-depth understanding of the needs of an evolving market.

As the tough gets going, and you need a manufacturer that can live up to tighter and tighter delivery times as well as products fit for the future, you can rest assured we are ready to deliver.


Do you want to know more?

Visit our website: www.prysmiangroup.com



PRYSMIAN

Prysmian Kabel und Systeme GmbH
Phone: +49 (0) 30 3675 40
kontakt@prysmiangroup.com



prysmiangroup.de

© All rights reserved by Prysmian 2024-01 | Version 2.

Technical data, dimensions and weights are subject to change. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian.

Follow us

