

Fast, flexible and safe.

TROMMELFLEX-M-PUR reeling cables
– a perfect hit.



The planet's pathways

TROMMELFLEX-M-PUR reeling cables – a perfect hit.

Our new low voltage 0.6/1 kV reeling cable is exceptionally well suited for frequently changing dynamic loads in underground mining operations, with a reeling speed of 60 m/min. TROMMELFLEX-M-PUR is highly flexible and lightweight. In addition, the cable is equipped with flame retardant and halogen-free polyurethane sheaths, a necessity in the underground environment. Touché!

TROMMELFLEX-M-PUR

Application

TROMMELFLEX-M-PUR is the new 0.6/1 kV reeling cable for underground mining and tunnelling equipment. It is specially designed for frequently changing dynamic loads such as reeling operations including drilling machines, scoops and LHD's.



MAIN FEATURES

- ✓ Suitable for underground reeling operations at the high speed of 60 m/min.
- ✓ Equipped with flame retardant, halogen-free polyurethane inner and outer sheath for rough environments
- ✓ Highly flexible and lightweight
- ✓ Very short length of lay for greater reeling performances

TROMMELFLEX-M-PUR D2X11Y 0.6/1 kV										
Number of cores x cross section	Part number	Conductor diameter max. mm	Outer diameter mm		Bending radius free moving min. mm	Weight (approx.) kg/km	Permissible tensile force max. N	Conductor resistance at 20 °C max. Ω/km	Current carrying capacity* A	Short circuit current (conductor) kA
			min.	max.						
3x25+3G6+2x1	20335531	6.2	22.5	24	192	1130	1500	0.7839	121	3.58
3x35+3G6+2x1.5	20335532	7.8	26.5	28	224	1530	2100	0.554	150	5.01
3X50+3G10+2X1.5	20333885	9.6	30	32	256	2160	3000	0.386	183	7.15
3x70+3G16+2x1.5	20335533	11.1	35	37	296	3050	4200	0.272	234	10.01
3x95+3G16+2x1.5	20335534	12.6	39.5	42	336	3690	5700	0.206	284	13.59
3x120+3G25+2x1.5	20335535	14.8	44	46.5	372	4810	7200	0.161	330	17.16
3x150+3G25+2x1.5	20335536	16	49	52	416	5960	9000	0.129	380	21.45
3x185+3G35+2x1.5	20335537	17.7	53.5	56	448	7300	11100	0.106	434	26.46
3x240+3G50+2x1.5	20335538	20.2	61.5	64.5	516	9600	14400	0.0801	512	34.32

* Nominal current carrying capacity for three-core cable laid on a surface, at 30 °C ambient temperature (see also IEC 60364-5-52).


TROMMELFLEX-M-PUR D2X11Y 0.6/1 kV	
Global data	
Brand	TROMMELFLEX-M-PUR
Type designation	D2X11Y
Design features	
Conductor	Bare electrolytic copper, finely stranded class 5 acc. to IEC 60228
Insulation	Cross linked polyethylene (XLPE), acc. to IEC 60502-1
Core identification	Main cores: brown, black, grey Control cores: blue, white
Core arrangement	Three main conductors laid-up together with split earth conductor and control cores in the interstices. Cores twisted with very short length of lay
Inner sheath	Polyurethane, halogen free, flame retardant, colour: white
Outer sheath	Polyurethane, halogen free, flame retardant, colour: yellow
Electrical parameters	
Rated voltage	0.6/1 kV (600/1000V)
Max. permissible operating voltage AC	0.7/1.2 kV
Max. permissible operating voltage DC	0.9/1.8
AC test voltage – main cores	2.5 kV (5 min.)

TROMMELFLEX-M-PUR D2X11Y 0.6/1 kV	
AC test voltage – control cores	1 kV
Current carrying capacity description	Acc. to DIN VDE 0298-4
Chemical parameters	
Performance against fire	Similar to IEC 60332-1-2
Water resistance	The cables are suitable for permanent use in water (no drinking water) up to 10 meter diving depth
Thermal parameters	
Max. operating temperature of the conductor	90 °C
Max. short circuit temperature of the conductor	250 °C
Ambient temperature for fixed installation	min. -40 °C, max. +80 °C
Ambient temperature in fully flexible operation	min. -30 °C, max. +80 °C
Mechanical parameters	
Max. tensile load on the conductor	20 N/mm ²
Torsional stress +/-	50 °/m
Bending radii min.	8 x D in reeling application
Travel speed	Reeling operation underground: 60 m/min. (for speed beyond please consult the manufacturer)



PRYSMIAN

Prysmian Kabel und Systeme GmbH
Phone: +49 (0) 30 3675 40
kontakt@prysmiangroup.com



prysmiangroup.de

© All rights reserved by Prysmian 2024-01 | Version 6.

Technical data, dimensions and weights are subject to change. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian.

Follow us

